## Eltax Summit

## Surround Loudspeakers 5-pack



## **Features**

- Complete loudspeaker surround system
- 2 way floorstanding bass reflex speakers
- · Magnetically shielded centre speaker
- Compact rear speaker
- Binding posts



System
Long term Max power
Short term Max power
Recommended power amplifier
Frequency range +/- 4 dB
Sensitivity (2,83V / 1M)
Impedance
Tweeter

Woofer Dimensions (HxWxD) Terminal type Centre

2 Way Closed Box 65 watts 100 watts

\_

80 - 20.000Hz 87dB 4 - 8 Ohm

25mm soft dome, neodynium 2 x 110mm shielded 135 x 360 x 197mm

Clip

Rear

2 Way Closed Box

60 watts 90 watts

-

80 - 20.000Hz 86dB

4 - 8 Ohm

25mm soft dome, neodynium

110mm 200 x 135 x 197

Clip

Front

2 Way Bassreflex

130 watts

250 watts

30 - 130 watts pr. Channel

45 - 20.000Hz

88 dB

4 - 8 Ohm

25mm soft dome, neodynium

2 x 165mm

840 x 210 x 250mm Biwiring Binding posts

All in 1 5 or 6-pack

2 way bassreflex

Biwiring posts